



877H SPECIFICATIONS >>>

ENGINE	
Model	2 / -
Power (kW)	1,700
Power (hp)	2,300
Rated Capacity (L)	20 (2 / 2) = 2,000 L
Rated Capacity (gal)	1,700 = 1,000 gal

TRANSMISSION	
Model	2 / -
Gear Ratio	2 / -

AXLES	
Front Axle	12"
Rear Axle	12"

STEERING	
Steering Type	20"

BRAKES	
Front Brakes	
Rear Brakes	

HYDRAULIC SYSTEM	
Flow (L/min)	20
Flow (gal/min)	1
Flow (gpm)	10

LOADER ARM PERFORMANCE with Standard Bucket 4.2 m³	
Capacity (m³)	1,200
Capacity (gal)	1,200
Capacity (L)	20
Capacity (gal)	1,100
Capacity (L)	1,000
Capacity (gal)	100
Capacity (L)	0
Capacity (gal)	0

BUCKET PERFORMANCE	
Capacity (m³)	2-7.0

DIMENSIONS	
Height (mm)	2,200
Height (in)	2,000
Height (mm)	2,000
Height (in)	2,000
Height (mm)	1,000
Height (in)	2
Height (mm)	1,000
Height (in)	1,200
Height (mm)	1,200

TIRES	
Size	2 - 2 / -

OPERATING WEIGHTS	
Weight (kg)	2,000

SERVICE CAPACITIES	
Capacity (L)	20
Capacity (gal)	0
Capacity (L)	2
Capacity (gal)	220
Capacity (L)	0
Capacity (gal)	2

